



Properties

Standards

Electro galvanized as per ASTM B 633

Galvanized as per ASTM A 123/ A 123M

Temperature resistance from - 20 °C to +100 °C

Noise reduction up to 18 dB (A)

Material

Steel

Finish

Electro Zinc Plated GI /
Hot dip galvanized HDG /
Stainless Steel A4

Applications

- For horizontal and vertical applications

Advantages

- The combination nut with thread M8/M10 allows for optimised mounting choices.
- The sound insulation insert offers noise protection and prevents contact corrosion.

Technical Data

Art number for GI	Art number for HG	Art number for SS	Nominal Pipe Size		Pipe Outside dia. (mm)	Clamping Range D (mm)	Thread G	Side Screw size (mm)	Max. Load (N)
			(inch)	(mm)					
3110018	3120018	3130018	3/8"	DN10	17.1	15-19	M8/M10	M6	1500
3110022	3120022	3130022	1/2"	DN15	21.3	20-25	M8/M10	M6	1500
3110028	3120028	3130028	3/4"	DN20	26.7	26-30	M8/M10	M6	1500
3110035	3120035	3130035	1"	DN25	33.4	32-36	M8/M10	M6	1500
3110040	3120040	3130040	1 1/4"	DN32	42.1	38-43	M8/M10	M6	1500
3110048	3120048	3130048	1 1/2"	DN40	48.2	47-51	M8/M10	M6	1500
3110054	3120054	3130054	-	-	54.0	53-58	M8/M10	M6	1500
3110060	3120060	3130060	2"	DN50	60.3	60-64	M8/M10	M6	1500
3110063	3120063	3130063	-	-	63.0	63-66	M8/M10	M6	2000
3110070	3120070	3130070	-	-	70.0	68-72	M8/M10	M6	2000
3110075	3120075	3130075	2 1/2"	DN65	73.0	74-80	M8/M10	M6	2000
3110083	3120083	3130083	-	-	83.0	81-86	M8/M10	M6	2000
3110090	3120090	3130090	3"	DN80	88.9	87-92	M8/M10	M6	2000
3110100	3120100	3130100	3 1/2"	DN90	101.6	99-105	M8/M10	M6	2000
3110110	3120110	3130110	-	-	110.0	107-112	M8/M10	M6	2000
3110115	3120115	3130115	4"	DN100	114.3	113-118	M8/M10	M6	2500
3110125	3120125	3130125	-	-	125.0	125-130	M8/M10	M6	2500
3110133	3120133	3130133	-	-	133.0	131-137	M8/M10	M6	2500
3110140	3120140	3130140	5"	DN125	141.3	138-142	M8/M10	M6	2500
3110150	3120150	3130150	-	-	150.0	148-153	M8/M10	M6	2500
3110160	3120160	3130160	-	-	160.0	159-166	M8/M10	M6	2500
3110168	3120168	3130168	6"	DN150	168.3	168-172	M8/M10	M6	2500
3110200	3120200	3130200	-	-	200.0	200-212	M8/M10	M8	3000
3110220	3120220	3130220	8"	DN200	219.1	215-220	M8/M10	M8	3000
3110250	3120250	3130250	-	-	250.0	249	M8/M10	M8	3000
3110315	3120315	3130315	-	-	315.0	313-318	M8/M10	M8	3000

Note :

Hot Dip Galvanized & Stainless Steel Finishes are available upon request