



Properties

Standards

Electro galvanized as per ASTM B 633

Galvanized as per ASTM A 123/ A 123M

Material

Steel

Finish

Electro Zinc Plated GI /
Hot dip galvanized HDG /
Stainless Steel A4

Applications

- For horizontal and vertical applications

Advantages

- Simple installation due to large opening angle.
- Strengthened lock bolts for high load capacity.
- Screws secured with anti-loss washer

Technical Data

Art number for GI	Nominal Pipe Size		Pipe Outside dia. (mm)	Clamping Range D (mm)	Thread G	Side Screw size (mm)	Max. Load (N)
	(inch)	(mm)					
3140018	3/8"	DN10	17.1	15-19	M8/M10	M6	1500
3140022	1/2"	DN15	21.3	20-25	M8/M10	M6	1500
3140028	3/4"	DN20	26.7	26-30	M8/M10	M6	1500
3140035	1"	DN25	33.4	32-36	M8/M10	M6	1500
3140040	1 1/4"	DN32	42.1	38-43	M8/M10	M6	1500
3140048	1 1/2"	DN40	48.2	47-51	M8/M10	M6	1500
3140054	-	-	54.0	53-58	M8/M10	M6	1500
3140060	2"	DN50	60.3	60-64	M8/M10	M6	1500
3140063	-	-	63.0	63-66	M8/M10	M6	2000
3140070	-	-	70.0	68-72	M8/M10	M6	2000
3140075	2 1/2"	DN65	73.0	74-80	M8/M10	M6	2000
3140083	-	-	83.0	81-86	M8/M10	M6	2000
3140090	3"	DN80	88.9	87-92	M8/M10	M6	2000
3140100	3 1/2"	DN90	101.6	99-105	M8/M10	M6	2000
3140110	-	-	110.0	107-112	M8/M10	M6	2000
3140115	4"	DN100	114.3	113-118	M8/M10	M6	2500
3140125	-	-	125.0	125-130	M8/M10	M6	2500
3140133	-	-	133.0	131-137	M8/M10	M6	2500
3140140	5"	DN125	141.3	138-142	M8/M10	M6	2500
3140150	-	-	150.0	148-153	M8/M10	M6	2500
3140160	-	-	160.0	159-166	M8/M10	M6	2500
3140168	6"	DN150	168.3	168-172	M8/M10	M6	2500
3140200	-	-	200.0	200-212	M8/M10	M8	3000
3140220	8"	DN200	219.1	215-220	M8/M10	M8	3000
3140250	-	-	250.0	249	M8/M10	M8	3000
3140315	-	-	315.0	313-318	M8/M10	M8	3000

Note :

Hot Dip Galvanized & Stainless Steel Finishes are available upon request